DS-252PR

Receipt Printing Scale





An ideal Weighing Solution for Retailers to enhance Speed & Quality of Customer Service











	Technical Specifications
No of PLUs / items	300
Preset keys / Hot keys	12
TAX / VAT rates	3
Power supply	230 VAC, 50 Hz
Power consumption	30 W max
Physical dimension	304(W) x 382(D) x 395(H) mm
Display type	7 Segment RED LED
Display digit and size	19 digits, 10 mm height
Number of keys	32
Rechargeable Battery	12 V/3.4 Ah
Printer	Direct thermal
Printing speed	50 mm/sec (max)
Reports	PLU sales, Total sales and PLU dump

Customer Display

DS-252PR

Capacity and Accuracy	Resolution	Tare value	Platter Size (mm)	Platter MOC
3 kg x 0.5 g	1/6000	- 1499.5 g	302 x 227	SS
6 kg x 1 g	1/6000	- 2.999 kg	302 x 227	SS
15 kg x 2 g	1/7500	- 7.498 kg	302 x 227	SS
30 kg x 5 g	1/6000	-14.995 kg	302 x 227	SS

Salient Features

Elevated-type Dust-proof printer housing
High speed reliable printer
 Upload and download PLU, Header / Footer and TAX settings through PC application software
High bright RED LED display for operator and customer

Paper roll Specification

Туре	Direct thermal
Width	57 mm (max)
Roll dia (OD)	40 mm (max)
Thickness	80 micron (max)

Printout Samples



Essae-Teraoka Pvt. Ltd.



410, 100ft Road, 4th Block, Koramangala, Bengaluru-560 034

• In-built Rechargeable battery



info@essae.com



http://www.essae.com



+91 80 2511 3021



1-800-425-3111



0-78488 12346



Your	Essae	representative
------	-------	----------------

